This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims (deleted text being struck through and added text being underlined):

(Currently Amended) A system comprising:

a portable computer including a keyboard and a computer chassis defining an interior, the computer chassis containing at least one heat generating component in the interior and having an internal speaker in the interior; and

openings in a wall of the chassis from which sound from produced by the speaker can emanate [[[,]]] from the interior of the chassis:

wherein the speaker is spaced from the wall of the chassis in which the openings allow are located to permit heat generated by the at least one heat generating component in the computer chassis to escape the interior of the computer chassis.

- 2. (Original) The system of claim 1 wherein the internal speaker is located at least a minimum distance away from the openings.
- 3. (Original) The system of claim 2 wherein the minimum distance is within the range of 5 to 20 mm.
- 4. (Original) The system of claim 1 comprising two internal speakers and openings proximate to each speaker.
- 5. (Previously Presented) The system of claim 4 wherein the openings are located on a front side surface of the portable computer.
- 6. (Previously Presented) The system of claim 2 wherein the openings are located on a top surface of the portable computer.

- 7. (Original) The system of claim 2 further comprising separate air intake vents located on the chassis.
- 8. (Original) The system of claim 7 wherein the air intake vents are located on one or more side surfaces of the chassis.
- 9. (Original) The system of claim 7 further comprising one or more ventilation fans located between the air intake vents and heat cooling components located inside the chassis.
- 10. (Original) The system of claim 4 further comprising one or more external speakers connectable to the chassis.
- 11. (Currently Amended) A portable computer system comprising:
 a portable computer chassis having an internal speaker including a

 cone with a concave front;
 - a heat generating device disposed within the chassis;
- a first opening in the chassis spaced apart from positioned in front of the internal speaker, wherein such that the first opening facilitates emanation of sound from the internal speaker to outside of the computer chassis, and wherein the front of the internal speaker is spaced from the first opening further facilitates to facilitate airflow along a first path between the internal speaker and the first opening; and
- a second opening in the chassis positioned to facilitate airflow between the second opening and the first opening along a further path past heat generated by the heat generating device within the computer chassis so as to remove heat generated by the heat generating device from within the computer chassis.
- 12. (Original) The portable computer system of claim 11 wherein the first opening is positioned on the chassis to minimize interference with airflow during common use of the portable computer system.

- 13. (Original) The portable computer system of claim 11 wherein the first opening comprises a grill.
- 14. (Previously Presented) The portable computer system of claim 11 and further comprising a third opening and a further speaker positioned proximate the third opening to promote airflow between the third opening and further speaker.
- 15. (Previously Presented) An electronic device comprising:
 a notebook computer having a chassis and a lid, the chassis containing
 at least one surface-mounted speaker grill located at least a minimum
 distance away from an internal speaker, the internal speaker being located
 in said chassis such that sound from the internal speaker can emanate from
 the surface-mounted speaker grill and heated air from heat generating
 components in the portable computer can flow out of the surface-mounted
 speaker grill.
 - 16. (Canceled)
- 17. (Previously Presented) The electronic device of claim 15 wherein the surface-mounted speaker grill is on a front side surface of the notebook computer.
- 18. (Previously Presented) The electronic device of claim 17 further comprising a further surface-mounted speaker grill on the front side surface, and a further internal speaker located at least said minimum distance away from said further surface-mounted speaker grill.

19. (Currently Amended) A method of ventilating a portable computer comprising:

providing a speaker grill on a surface of a portable notebook computer, including a keyboard, in a position such that the grill is disposed within an airflow exhaust path; path for the computer:

spacing a front of a speaker away from the speaker grill on the surface of the portable notebook computer so that the airflow exhaust path extends between the front of the speaker and the speaker grill; and

venting heated air in the airflow exhaust path out through the speaker grill.

- 20. (Original) The method of claim 19 wherein the speaker grill is not located on a bottom surface of the portable computer.
- 21. (Previously Presented) The method of claim 20 wherein the speaker grill is on a front side surface of the portable computer.
- 22. (Original) The method of claim 20 wherein the speaker grill is on a side surface or top surface of the portable computer.
- 23. (Original) The method of claim 19 further comprising connecting an internal speaker to the portable computer at least a minimum distance away from the speaker grill.
- 24. (Original) The method of claim 19 comprising two speaker grills, each with a speaker located at least the minimum distance away.
- 25. (Previously Presented) The method of claim 19 further comprising an airflow intake path wherein cool air is drawn in through one or more separate air intake vents and directed to heat cooling components and wherein said airflow intake path leads to said airflow exhaust path.

- 26. (Original) The method of claim 25 further comprising providing a ventilation fan in the airflow intake path.
- 27. (Previously Presented) The method of claim 2 wherein said openings are located on at least one side surface of the portable computer.
- 28. (New) The system of claim 1 wherein the speaker has a front from which sound generated by the speaker is emanated, and the openings in the wall of the chassis are positioned in front of the speaker.
- 29. (New) The system of claim 1 wherein the speaker has an axis along which sound is directed from the speaker, the openings in the wall of the chassis being positioned adjacent to an intersection of the axis and the wall of the chassis.
- 30. (New) The system of claim 1 wherein the speaker is configured in the computer chassis such that a flow of air moving through an interior of the computer chassis is capable of moving between the speaker and the openings in the chassis.